

SAFETY DATA SHEET**A00807 MST WAX OFF GLD WX STPR 20net18**

Version 1.0

Revision Date 03/04/2015

Print Date 06/30/2015

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Material name : A00807 MST WAX OFF GLD WX STPR 20net18

Material number : 000000000001033964

Manufacturer or supplier's details

Company : Zep Inc.

Address : 1310 Seaboard Industrial Blvd., NW
Atlanta, GA 30318

Telephone : 404-352-1680

Emergency telephone numbers**For SDS Information** : Compliance Services 1-877-428-9937**For a Medical Emergency** : 877-541-2016 Toll Free - All Calls Recorded**For a Transportation Emergency** : CHEMTREC: 800-424-9300 - All Calls Recorded.
In the District of Columbia 202-483-7616**SECTION 2. HAZARDS IDENTIFICATION****Emergency Overview**

Appearance	Aerosol containing a liquefied gas
Colour	clear
Odour	mint-like

GHS ClassificationFlammable aerosols : Category 2
Gases under pressure : Liquefied gas
Skin irritation : Category 2
Serious eye damage : Category 1**GHS Label element**

Hazard pictograms :



Signal word : Danger

Hazard statements : H223 Flammable aerosol.
H280 Contains gas under pressure; may explode if heated.
H315 Causes skin irritation.
H318 Causes serious eye damage.Precautionary statements : **Prevention:**
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Pressurized container: Do not pierce or burn, even after

SAFETY DATA SHEET**A00807 MST WAX OFF GLD WX STPR 20net18**

Version 1.0

Revision Date 03/04/2015

Print Date 06/30/2015

use.

P264 Wash skin thoroughly after handling.

P280 Wear eye protection/ face protection.

P280 Wear protective gloves.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/ physician.

P332 + P313 If skin irritation occurs: Get medical advice/ attention.

P362 Take off contaminated clothing and wash before reuse.

Storage:

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

Potential Health Effects**Carcinogenicity:****IARC**

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

ACGIH

Confirmed animal carcinogen with unknown relevance to humans

OSHA

2-butoxyethanol

111-76-2

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

NTP

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical Name	CAS-No.	Concentration [%]
2-butoxyethanol	111-76-2	>= 10 - < 20
butane	106-97-8	>= 10 - < 20
2-aminoethanol	141-43-5	>= 1 - < 5
propane	74-98-6	>= 1 - < 5

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.
 Show this safety data sheet to the doctor in attendance.
 Do not leave the victim unattended.

If inhaled : Consult a physician after significant exposure.
 If unconscious place in recovery position and seek medical

SAFETY DATA SHEET**A00807 MST WAX OFF GLD WX STPR 20net18**

Version 1.0

Revision Date 03/04/2015

Print Date 06/30/2015

advice.

- In case of skin contact : If skin irritation persists, call a physician.
Wash off immediately with plenty of water for at least 15 minutes.
If on clothes, remove clothes.
- In case of eye contact : Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
Rinse immediately with plenty of water for at least 15 minutes.
- If swallowed : Keep respiratory tract clear.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
DO NOT induce vomiting unless directed to do so by a physician or poison control center.
Take victim immediately to hospital.

SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical
Water spray jet
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : Carbon dioxide (CO₂)
Carbon monoxide
Smoke
Nitrogen oxides (NO_x)
- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
- Further information : Standard procedure for chemical fires.
- Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Ensure adequate ventilation.
Remove all sources of ignition.
Evacuate personnel to safe areas.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

SAFETY DATA SHEET**A00807 MST WAX OFF GLD WX STPR 20net18**

Version 1.0

Revision Date 03/04/2015

Print Date 06/30/2015

- Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Sweep up or vacuum up spillage and collect in suitable container for disposal.

SECTION 7. HANDLING AND STORAGE

- Advice on safe handling : Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Do not breathe vapours or spray mist.
Take precautionary measures against static discharges.
Provide sufficient air exchange and/or exhaust in work rooms.
Dispose of rinse water in accordance with local and national regulations.
Always replace cap after use.
- Conditions for safe storage : BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects.
No smoking.
Observe label precautions.
Keep in a dry, cool and well-ventilated place.
Electrical installations / working materials must comply with the technological safety standards.
- Materials to avoid : Do not store near acids.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**Components with workplace control parameters**

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
2-butoxyethanol	111-76-2	TWA	20 ppm	ACGIH
		TWA	5 ppm 24 mg/m ³	NIOSH REL
		TWA	50 ppm 240 mg/m ³	OSHA Z-1
		TWA	25 ppm 120 mg/m ³	OSHA P0
butane	106-97-8	TWA	800 ppm 1,900 mg/m ³	NIOSH REL

SAFETY DATA SHEET



A00807 MST WAX OFF GLD WX STPR 20net18

Version 1.0

Revision Date 03/04/2015

Print Date 06/30/2015

		TWA	800 ppm 1,900 mg/m3	OSHA P0
2-aminoethanol	141-43-5	TWA	3 ppm	ACGIH
		STEL	6 ppm	ACGIH
		TWA	3 ppm 8 mg/m3	NIOSH REL
		ST	6 ppm 15 mg/m3	NIOSH REL
		TWA	3 ppm 6 mg/m3	OSHA Z-1
		STEL	6 ppm 15 mg/m3	OSHA P0
		TWA	3 ppm 8 mg/m3	OSHA P0
propane	74-98-6	TWA	1,000 ppm	ACGIH
		TWA	1,000 ppm 1,800 mg/m3	NIOSH REL
		TWA	1,000 ppm 1,800 mg/m3	OSHA Z-1
		TWA	1,000 ppm 1,800 mg/m3	OSHA P0

Biological occupational exposure limits

Component	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
2-BUTOXYETHANOL	111-76-2	Butoxyacetic acid (BAA)	Urine	End of shift (As soon as possible after exposure ceases)	200 mg/g	ACGIH BEI
Remarks: Creatinine						

Personal protective equipment

- Respiratory protection : In case of insufficient ventilation, wear suitable respiratory equipment.
- Hand protection
Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.
- Eye protection : Ensure that eyewash stations and safety showers are close to the workstation location.
Tightly fitting safety goggles
- Skin and body protection : impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.
- Hygiene measures : When using do not eat or drink.
When using do not smoke.
Wash hands before breaks and at the end of workday.

SAFETY DATA SHEET**A00807 MST WAX OFF GLD WX STPR 20net18**

Version 1.0

Revision Date 03/04/2015

Print Date 06/30/2015

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: Aerosol containing a liquefied gas
Colour	: clear
Odour	: mint-like
Odour Threshold	: no data available
pH	: 12
Melting point/freezing point	: no data available
Boiling point	: no data available
Flash point	: no data available
Evaporation rate	: no data available
Upper explosion limit	: no data available
Lower explosion limit	: no data available
Vapour pressure	: no data available
Relative vapour density	: no data available
Density	: no data available
Solubility(ies)	
Water solubility	: completely soluble
Partition coefficient: n-octanol/water	: no data available no data available
Auto-ignition temperature	: not determined
Thermal decomposition	: no data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: Stable
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: No decomposition if stored and applied as directed. Vapours may form explosive mixture with air.
Conditions to avoid	: Heat, flames and sparks. Extremes of temperature and direct sunlight.
Incompatible materials	: Acids Copper
Hazardous decomposition products	: Carbon oxides Nitrogen oxides (NO _x)

SAFETY DATA SHEET**A00807 MST WAX OFF GLD WX STPR 20net18**

Version 1.0

Revision Date 03/04/2015

Print Date 06/30/2015

SECTION 11. TOXICOLOGICAL INFORMATION**Acute toxicity****Product:**

Acute oral toxicity : Acute toxicity estimate : 2,544 mg/kg
Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate : 7.63 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate : > 5,000 mg/kg
Method: Calculation method

Skin corrosion/irritation**Product:**

Remarks: Irritating to skin.

Serious eye damage/eye irritation**Product:**

Remarks: May cause irreversible eye damage.

Respiratory or skin sensitisation

no data available

Germ cell mutagenicity

no data available

Carcinogenicity

no data available

Reproductive toxicity

no data available

2-butoxyethanol:

butane:

2-aminoethanol:

propane:

STOT - single exposure

no data available

STOT - repeated exposure

no data available

Aspiration toxicity

SAFETY DATA SHEET**A00807 MST WAX OFF GLD WX STPR 20net18**

Version 1.0

Revision Date 03/04/2015

Print Date 06/30/2015

no data available

Further information**Product:**

Remarks: no data available

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity**

no data available

Persistence and degradability

no data available

Bioaccumulative potential**Product:**

Partition coefficient: n-octanol/water : Remarks: no data available

Remarks: no data available

Components:**butane :**

Partition coefficient: n-octanol/water : Pow: 2.89

Mobility in soil

no data available

Other adverse effects

no data available

Product:

Regulation

40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances

Remarks

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological information

: no data available

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

Waste from residues

: Dispose of in accordance with local regulations.

SAFETY DATA SHEET**A00807 MST WAX OFF GLD WX STPR 20net18**

Version 1.0

Revision Date 03/04/2015

Print Date 06/30/2015

Contaminated packaging : Empty remaining contents.
 Dispose of as unused product.
 Do not re-use empty containers.
 Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

Transportation Regulation: 49 CFR (USA):
 ORM-D, CONSUMER COMMODITY

Transportation Regulation: IMDG (Vessel):
 UN1950, AEROSOLS, 2.1, - Limited quantity

Transportation Regulation: IATA (Cargo Air):
 UN1950, Aerosols, flammable, 2.1, - Limited quantity

Transportation Regulation: IATA (Passenger Air):
 UN1950, Aerosols, flammable, 2.1, - Limited quantity

Transportation Regulation: TDG (Canada):
 UN1950, AEROSOLS, 2.1, - Limited quantity

SECTION 15. REGULATORY INFORMATION**EPCRA - Emergency Planning and Community Right-to-Know Act****CERCLA Reportable Quantity**

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
2,2'-iminodiethanol	111-42-2	100	*

*: Calculated RQ exceeds reasonably attainable upper limit.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Fire Hazard
 Sudden Release of Pressure Hazard
 Acute Health Hazard

SARA 302 : SARA 302: No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 : SARA 313: This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

SAFETY DATA SHEET**ZepInc****A00807 MST WAX OFF GLD WX STPR 20net18**

Version 1.0

Revision Date 03/04/2015

Print Date 06/30/2015

California Prop 65

WARNING! This product contains a chemical known to the State of California to cause cancer.

2,2'-iminodiethanol


111-42-2

The components of this product are reported in the following inventories:

TSCA	On TSCA Inventory
DSL	This product contains one or several components that are not on the Canadian DSL nor NDSL.
AICS	Not in compliance with the inventory
NZIoC	Not in compliance with the inventory
PICCS	Not in compliance with the inventory
IECSC	Not in compliance with the inventory

Inventory Acronym and Validity Area Legend:

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TSCA (USA)

SECTION 16. OTHER INFORMATION**Further information****NFPA:****HMIS III:**

HEALTH	3
FLAMMABILITY	3
PHYSICAL HAZARD	2

0 = not significant, 1 = Slight,
2 = Moderate, 3 = High
4 = Extreme, * = Chronic

OSHA GHS Label Information:

Hazard pictograms



Signal word

: **Danger:**

Hazard statements

: Flammable aerosol. Contains gas under pressure; may explode if heated. Causes skin irritation. Causes serious eye damage.

Precautionary statements

: **Prevention:** Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Wash skin thoroughly after handling. Wear eye protection/ face protection. Wear protective gloves.

Response: IF ON SKIN: Wash with plenty of soap and water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/physician. If

SAFETY DATA SHEET**A00807 MST WAX OFF GLD WX STPR 20net18**

Version 1.0

Revision Date 03/04/2015

Print Date 06/30/2015

skin irritation occurs: Get medical advice/ attention. Take off contaminated clothing and wash before reuse.

Storage: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes.

This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.

Zep Inc. markets products under well recognized and established brand names such as Zep®, Zep Commercial®, Zep Professional®, Enforcer®, National Chemical™, Selig™, Misty®, Next Dimension™, Petro®, i-Chem®, TimeMist®, TimeWick™, MicrobeMax®, Country Vet®, Konk®, Original Bike Spirits®, Blue Coral®, Black Magic®, Rain-X®, Niagara National™, FC Forward Chemicals®, Rexodan®, Mykal™, and a number of private labeled brands.